



Version with Markings to
Show Changes Made

DESCRIPTION

CONTROL METHOD OF GENERATOR

Technical Field

5 The present invention relates to a controlling method of a generator which has an SR motor (Switched Reluctance Motor) structure.

Background Art

10 Recently, in an electric automobile or a so-called hybrid car in which a motor and an engine are commonly used, it has been discussed not to use an expensive permanent magnet, but to use an SR motor that has a simple and rigid structure, and excels in a high speed rotation and an environmental resistance.

15 Generally, the SR motor has a construction ~~that~~ in which a rotor made of magnetic steel sheet is disposed rotatably coaxially with a stator inside the stator in which a coil is wound around. Salient poles projecting inward are formed on an inner peripheral side of the stator, and a coil is wound around on

20 this salient pole to form a winding. Salient poles projecting outward are formed radially on an outer periphery of the rotor, and adapted to approach, oppose and separate from the salient poles of the stator in association with the rotation of the rotor. The salient poles of the rotor and the salient poles of

25 the stator are set to even numbers so that both the salient poles of the rotor and the salient poles of stator do not have a multiple relation with each other with the result that when certain salient poles of the stator and the rotor are opposed, the other salient poles of the stator and the rotor are deviated

at the positions. That is, when the number of salient poles of the rotor is, for example, four, the number of salient poles of the stator is set to six, and when the number of salient poles of the rotor is six, the number of salient poles of the stator
5 is set to eight.

In such an SR motor, when current flows, for example, to a pair of the opposed windings of the stator, a magnetic flux directed from the salient pole of the stator toward the salient pole of the rotor is generated. Thus, the salient pole of the
10 rotor is attracted to the salient pole of the stator to generate a torque at the rotor. As described above, the salient poles of the stator and the rotor are set so that when certain salient poles are opposed, a deviation arises at the other salient poles. Therefore, the winding of the salient pole set to the state that
15 the other salient poles are deviated, is applied with power, the salient poles of the deviated state are attracted, and thus the rotor is rotated. When this operation is continuously conducted, the salient poles of the rotor are attracted to the salient poles of the stator continuously, and the rotor is rotated
20 around its axis.

On the other hand, such an SR motor can be used as a generator, for example, Japanese Patent Application Laid-Open Publication No. 2001-57795 and Japanese Patent Application Laid-Open Publication No. 2001-78490, disclose a control system for
25 preventing overcurrent at a power generation time and thereby generating electricity in a high efficiency. In the Publication No. 2001-57795, a maximum amount of current, when a power regeneration is conducted at present time, is predicted and calculated based on a rotational speed of the rotor or on an

amount of supply current during a supply mode for ~~functioning~~
using the SR motor as a motor by supplying a power from a
battery. When the maximum amount of current reaches a
predetermined rate, a regenerative mode ~~that~~ in which an
5 electromotive force generated in the winding is recovered ~~to~~ in
the battery is performed.

In the Publication No. 2001-78490, in addition to the
above-mentioned supply mode and regenerative mode, a reflux mode
in which both ends of the winding are set to the same potential,
10 is set. At the reflux mode time, the winding is short circuited,
and hence winding current increases. A winding current value is
always monitored. After the supply mode is switched to the
regenerative mode, and when the winding current value reaches a
lower limit value, the regenerative mode is switched to the
15 above-mentioned reflux mode. In the reflux mode, a current
value rises, and when the current value reaches an upper limit
value, the reflux mode is again switched to the regenerative
mode. This switching of the regenerative mode and the reflux
mode is continued until the rotor becomes a predetermined rotary
20 angle. Thus, the winding current value is controlled between
the upper limit value and the lower limit value so as to prevent
the winding current from becoming large in a projecting manner.

Meanwhile, in the above-mentioned control system, in an
inductance reducing region ($dL/d\theta < 0$), the current is controlled
25 to fall within a predetermined range by means of the alternating
mode and the reflux mode, and thereafter regenerative current
flows. Since the current flowing in the range of $dL/d\theta < 0$
affects a braking force to the rotor, it is necessary to
suppress a control current value in the alternating/reflux mode

to raise a power generating efficiency. However, when this control current value is suppressed to a small value, the regenerative current value is also reduced, and hence there is a problem that it becomes difficult to assure a necessary amount of power generation. In order to control a motor current, a sensor for detecting the current value and a feedback control circuit which is operated at a high speed are necessary. Hence, there is a problem that the apparatus becomes expensive. An object of the present invention is to improve a power generating efficiency of a generator having an SR motor structure.

Disclosure-Summary of the Invention

A controlling method of a generator according to the present invention having a stator that has a plurality of salient poles, a rotor that has a plurality of salient poles of ~~the~~ a number (quantity) different from the salient poles of the stator, and a winding wound around the stator, comprises: executing a reflux mode at both ends of the winding set to the same potential after executing a supply mode for supplying a power from a power source to the winding; and, after the reflux mode, executing a regenerative mode for recovering an electromotive force generated in the winding to the power source.

In the present invention, after the supply mode is conducted, the reflux mode is executed, and thereafter the regenerative mode is carried out. In this manner, the regenerative mode is executed after the reflux mode is performed, the amount of current is raised once by the reflux mode after a supply mode is conducted, the regenerative mode is then carried out, and an amount of the regenerative energy in the

regenerative mode can be increased, and hence the power generating efficiency is improved.

Further, another controlling method of a generator according to the present invention having a stator that has a plurality of salient poles, a rotor that has a plurality of salient poles of ~~the~~a number different from the salient poles of the stator, and a winding wound around the stator, comprises: executing an alternating mode for alternately repeating a supply mode for supplying a power from a power source to the winding and a reflux mode for setting both ends of the winding to the same potential; and, after the alternating mode, further executing the reflux mode, thereafter executing a regenerative mode for recovering the electromotive force generated in the winding to the power source.

In the present invention, an average current value in a region where the brake force by the winding current is generated is being suppressed by the alternating mode, and the regenerative mode is executed after the reflux mode is performed to raise the current value. Here, a rising trend of the amount of current in the reflux mode is determined according to the current value and the rotational speed of the rotor at the reflux mode starting time. If they are not sufficiently large, the amount of current does not increase at the reflux mode time. When the increase in the current at the reflux mode time is not sufficient, the amount of the regenerative energy in the regenerative mode cannot be secured, and the power generating efficiency decreases. Meanwhile, when the winding current is controlled to increase the amount of current at the reflux mode starting time, the brake force increases accordingly.

In the controlling method of the present invention, the alternating mode for alternatively repeating the supply mode and the reflux mode is executed, and after this alternating mode, the reflux mode is further performed, and thereafter the
5 regenerative mode is carried out. Therefore, the amount of current can be increased at the reflux mode starting time while suppressing the brake force in the alternating mode, the brake force and the amount of the regenerative energy are controlled in a well-balanced manner, and the power generating efficiency
10 can be improved.

In the controlling method of the generator, the generator is controlled by a switching circuit having a switching element and a diode connected to both ends of the winding, and the switching element is PWM controlled, to thereby execute the
15 alternating mode.

In the controlling method of the generator, the voltage of the power source is detected, and a continuation time of one or both of the supply mode and the reflux mode or one or both of the alternating mode and the reflux mode may be controlled based
20 on the voltage value. Thus, the overcharging of the power source in the regenerative mode can be prevented.

Furthermore, another controlling method of a generator according to the present invention having a stator that has a plurality of salient poles, a rotor that has a plurality of
25 salient poles of ~~the~~ a number different from the salient poles of the stator, and a winding wound around the stator, comprises: executing a first alternating mode for alternately repeating a supply mode for supplying a power from a power source to the winding and a reflux mode for setting both ends of the winding

to the same potential; and after the first alternating mode, executing a second alternating mode for alternately repeating the reflux mode and the regenerative mode for recovering the electromotive force generated in the winding to the power source.

5 In the present invention, since the second alternating mode is provided after the first alternating mode and the reflux mode and the regenerative mode are repeated in this second alternating mode, a rise of the current in the reflux mode can be suitably suppressed in the regenerative mode. Therefore, the
10 regenerative current rate can be secured to the maximum while suitably suppressing the maximum current rate, and power generation in a well-balance manner between them can be performed. Accordingly, a load on a power device is reduced, an element having a large capacity is not required, and its cost
15 can be reduced. Further, a winding current rate can be suppressed without adding a current sensor, a high-speed comparator or the like, and an increase in cost due to the increase in the number of components can be prevented.

 In the controlling method of the generator, the generator
20 is controlled by a switching circuit having a switching element and a diode connected to both ends of the winding, and the switching element is PWM controlled to thereby execute the first and second alternating modes.

 In the controlling method of the generator, the first
25 alternating mode may be started before the time point ~~that~~at which the inductance of the winding becomes maximum. The first alternating mode is advanced from a time point ~~that~~at which an inductance becomes maximum in this manner, the continuation time of the first alternating mode is lengthened. Therefore, since

the current rate at the second alternating mode starting time increases and a power generation rate can be increased, the present method is particularly effective in the case where the power generation rate is insufficient. Meanwhile, since the
5 increase in the current rate in the second alternating mode is suppressed, even when the winding current rate is excessively increased due to a lead angle, the current rate can be suitably suppressed. Therefore, according to the present invention, the increase in the current rate due to the lead angle and the
10 suppression of the current rate in the second alternating mode are combined in a well-balanced manner, ~~therefore,~~ so that it is possible to realize a preferable control state capable of sufficiently maintaining a regenerative current rate while suppressing the maximum current value.

15

Brief Description of the Drawings

FIG. 1 is an explanatory view showing a construction of a generator applied with a controlling method of an embodiment 1 of the present invention;

20 FIG. 2 is a circuit diagram showing a construction of a drive circuit in the generator of FIG. 1;

FIG. 3 is a circuit diagram showing only a U-phase portion extracted from the circuit diagram of FIG. 2; wherein (a) shows a supply mode, (b) shows a regenerative mode, and (c)
25 shows a reflux mode in the controlling method of the embodiment 1;

FIG. 4 is an explanatory view showing execution timing of each mode in any one of U-phase, V-phase and W-phase; wherein (a) shows the relationship between a rotary angle of a rotor and

an inductance L, (b) shows the relationship between the rotary angle of the rotor and the winding applying voltage, and (c) shows the relationship between the rotary angle of the rotor and the winding current;

5 FIG. 5 is an explanatory view showing execution timing of each mode in the controlling method of the embodiment 1; wherein (a) shows the relationship between the rotary angle of the rotor and the inductance L, (b) shows the energizing state of HI side and LO side in the drive circuit, (c) shows the relationship
10 between the rotary angle of the rotor and the winding voltage, and (d) shows the relationship between the rotary angle of the rotor and the winding current;

 FIG. 6 is a circuit diagram showing only the U-phase portion extracted from the circuit diagram of FIG. 2; wherein
15 (a) shows the supply mode, (b) shows the regenerative mode and (c) and (d) show reflux mode in the controlling method of an embodiment 2;

 FIG. 7 is an explanatory view showing execution timing of each mode in the controlling method of the embodiment 2 of the
20 present invention; wherein (a) shows the relationship between the rotary angle of the rotor and the inductance L, (b) shows the energizing state of the HI side and the LO side in the drive circuit, (c) shows the relationship between the rotary angle of the rotor and the winding voltage, and (d) shows the
25 relationship between the rotary angle of the rotor and the winding current; and

 FIG. 8 is an explanatory view showing execution timing of each mode in the controlling method of an embodiment 3 of the present invention; wherein (a) shows the relationship between

the rotary angle of the rotor and the inductance L, (b) shows the energizing state of the HI side and the LO side in the drive circuit, (c) shows the relationship between the rotary angle of the rotor and the winding voltage, and (d) shows the
5 relationship between the rotary angle of the rotor and the winding current.

Best Mode for Carrying Out Detailed Description of the Invention

(Embodiment 1)

10 Now, the embodiments of the present invention will be described in detail with reference to the accompanying drawings. FIG. 1 is an explanatory view showing a construction of a generator applied with a controlling method of an embodiment 1 of the present invention. A generator 1 of FIG. 1 has a
15 structure similar to a so-called SR motor, and comprises a stator 2, and a rotor 3 that is rotatably arranged inside the stator 2. The stator 2 is contained in a housing (not shown). The generator 1 is driven, for example, by an automobile engine. In this case, the rotor 3 is coupled to a crankshaft of the
20 engine. The generator 1 of this embodiment is an inner rotor type, but may be an outer rotor type in which the positional relationship between the stator and the rotor is opposite.

The stator 2 has a stator core 4 and a plurality of windings 5. The stator core 4 is formed by laminating a
25 plurality of magnetic steel sheets, and fixed in the housing. The stator core 4 has a cylindrical yoke 6 and six salient poles 7 at the inside of the yoke 6. The salient poles 7 inwardly project toward the radial direction of the yoke 6. The winding 5 is formed by winding a coil on each salient pole 7. The

generator 1 is a three-phase generator, and the winding 5 has U-phase, V-phase and W-phase windings 5Ua, 5Ub, 5Va, 5Vb, 5Wa, and 5Wb. A pair of opposed windings 5 are connected in series to construct the respective phase winding sets 5U, 5V and 5W.

5 The rotor 3 has a shaft 8 and a rotor core 9. The shaft 8 is rotatably supported by bearings provided in the housing. The rotary angle of the shaft 8 is detected by a shaft position sensor 17 (refer to FIG. 2). A rotational speed of the rotor 3 can be calculated from a period and a pulse width of the shaft
10 position sensor 17. Incidentally, if a rotational speed detecting sensor is separately provided, it may be utilized. The rotor core 9 is formed by laminating a plurality of magnetic steel sheets, and fixed to the shaft 8. Four salient poles 10 are provided on an outer peripheral side of the rotor core 9.
15 The rotor 3 is coaxially inserted and placed ~~to~~in the stator 2, and a predetermined gap is formed between the salient pole 10 and the salient pole 7 of the stator 2.

Such a generator 1 can be used as an SR motor by sequentially supplying current to windings 5 of the respective
20 phases. Here, when the current flows to the winding 5, a magnetic flux is generated directed from the salient pole 7 of the stator 2 to the salient pole 10 of the rotor 3. For example, when the windings 5Va, 5Vb are applied with power in a state shown in FIG. 1, the salient poles 10b of the rotor 3 located
25 near the windings are attracted, a torque is generated, and hence the rotor 3 moves in a counterclockwise direction. When the salient pole 7V of the stator 2 is opposed to the salient pole 10b of the rotor 3, a positional displacement arises between the salient poles 7W and 10a since the stator 2 has six

poles and the rotor 3 has four poles.

When the windings 5Wa, 5Wb of the salient pole 7W are applied with power, then the salient pole 10a is attracted to the salient pole 7W. At this time, a positional displacement
5 arises between the salient poles 7U and 10b. Next, when the windings 5Ua, 5Ub of the salient pole 7U are applied with power, the salient pole 10b is attracted to the salient pole 7U. That is, when the windings 5 of the respective phases are sequentially applied with power, the salient poles 10 of the
10 rotor 3 are continuously attracted to the salient poles 7 of the stator 2, the rotor 3 rotates with the shaft 8 in the stator 2, and operates as the SR motor.

FIG. 2 is a circuit diagram showing a construction of a drive circuit in the generator of FIG. 1. As shown in FIG. 2,
15 switching circuit 19 having FETs (switching elements) and diodes is connected to both ends of the winding sets 5U, 5V and 5W of the respective phases. ~~One~~ The first end sides (HI side: UH, VH and WH) of the winding sets 5U, 5V and 5W are connected to a positive (+) electrode of a battery (power source) 16 through
20 the FETs 11U, 11V and 11W, respectively and also connected (grounded) to a negative (-) electrode of the battery 16 through the diodes 13U, 13V and 13W, respectively. The other (second) end sides (LO side: UL, VL and WL) of the winding sets 5U, 5V and 5W are connected to the positive electrode of the battery 16
25 through the diodes 14U, 14V and 14W, and also connected to the negative electrode of the battery 16 through the FETs 12U, 12V and 12W, respectively.

The FETs 11 and 12 are controlled by gate drivers 15U, 15V and 15W. The gate drivers 15U, 15V and 15W are connected to

a CPU 18, and controlled by the CPU 18. The generator 1 further has a shaft position sensor 17 which can detect the rotary angle of the shaft 8. The output of the shaft position sensor 17 is inputted to the CPU 18. The CPU 18 controls the gate drivers
5 15U, 15V and 15W based on the detection signal, and suitably applies power to the winding sets 5U, 5V and 5W. The CPU 18 calculates the rotational speed of the shaft 8 from the signal of the shaft position sensor 17. Incidentally, a voltage of the battery 16 is monitored by the CPU 18 at all times.

10 FIG. 3 is a circuit diagram showing only the U-phase portion extracted from the circuit diagram of FIG. 2, FIG. 3(a) shows the supply mode, FIG. 3(b) shows the regenerative mode, and FIG. 3(c) shows the reflux mode. Incidentally, the following description will be made only for the U-phase, and the
15 V-phase and the W-phase are operated similarly to the U-phase. In the controlling method, the generator 1 is driven by three control modes of the supply mode, the regenerative mode and the reflux mode. The supply mode supplies power to the winding set 5U, the regenerative mode recovers an electromotive force
20 generated in the winding set 5U, and the reflux mode short circuits both ends of the winding set 5U as the same potential.

In the supply mode, as shown in FIG. 3(a), the FETs 11U and 12U are turned ON simultaneously. In this mode, a current flows in a route through the FET 11U, the winding set 5U and the
25 FET 12U. Thus, the battery 16 supplies power to the windings 5Ua, 5Ub of the winding set 5U, the salient poles 10 of the rotor 3 are attracted to the salient poles 7U of the stator 2, and hence the rotor 3 is rotated or braked.

In the regenerative mode, as shown in FIG. 3(b), the FETs

11U, 12U are turned OFF simultaneously. When the FETs 11U, 12U are turned OFF, a power supply from the battery 16 to the winding set 5U is stopped. At this time, an electromotive force for holding the magnetic flux is generated in the winding set 5U.

5 In this mode, a current flows in a route through the diode 13U, the winding set 5U and the diode 14U by this electromotive force. Thus, an energy is regenerated in the battery 16.

In the reflux mode, as shown in FIG. 3(c), the FET 11U is turned OFF, and the FET 12U is turned ON. Even in this state,
10 the power supply from the battery 16 to the windings 5Ua, 5Ub is stopped, and an electromotive force is generated in the windings 5Ua, 5Ub. In this mode, a current flows in a route through the diode 13U, the winding set 5U, the FET 12U by this electromotive force. That is, both ends of the winding set 5U are grounded,
15 and the current refluxes through the aforementioned route during the reflux mode. Incidentally, the FET 11U may be turned ON, and the FET 12U may be turned OFF to perform the reflux mode.

In the controlling method of the generator according to the present invention, the above-mentioned three types of the
20 modes are performed as described below:—FIG. 4 is an explanatory view showing execution timing of each mode in any one of U-phase, V-phase and W-phase, any of the abscissa axes show a rotary angle of the rotor 3. FIG. 4(a) shows the relationship between the rotary angle of the rotor and the
25 inductance L, FIG. 4(b) shows the relationship between the rotary angle of the rotor and the winding applying voltage, and FIG. 4(c) shows the relationship between the rotary angle of the rotor and the winding current.

As shown in FIG. 4, in this embodiment, when the

inductance L becomes the maximum value L_{\max} (change rate $(dL/d\theta)$ of the inductance L is "0"), the power supply to the winding 5 is started. The power supply to the winding 5 is PWM controlled by the gate drivers 15U, 15V and 15W. That is, the supply
5 current rate to the winding 5 is controlled by the continuation time and the duty ratio under the ON/OFF control of the FET 11U or the like, and the alternating mode for alternatively repeating the supply mode and the reflux mode is executed. The continuation time T_d of the alternating mode is set in response
10 to the rotational speed of the rotor calculated from the signal of the shaft position sensor 17. At this time, T_d can be set by the rotary angle of the rotor, and may be set to a predetermined angle irrespective of the rotational speed or to an angle in response to the rotational speed.

15 At the supply mode execution time (portion P in FIG. 4(c)) during the alternating mode, the winding current increases, while at the reflux mode execution time (portion Q in FIG. 4(c)), the winding current decreases. Here, the reduction part of the winding current in the reflux mode is smaller than the increase
20 part of the winding current in the supply mode, and during the alternating mode, the PWM duty ratio is set so that the current waveform to generally increases in the sawtooth-like waveform.

After the time T_d is elapsed, the CPU 18 stops the PWM control, and only the reflux mode is performed. Thus, the
25 current flowing to the winding 5 increases. After the reflux mode is performed for a predetermined period (or a predetermined rotary angle of the rotor), the regenerative mode is executed. When the regenerative mode is performed, the winding voltage becomes $-E$, and the winding current i is gradually decreased to

become "0" shortly. Thus, an energy of an amount shown by an area of a portion R of FIG. 4(c) is regenerated to the battery 16. Since the amount of the regenerative energy is determined depending upon the current rate at the regenerative mode starting time, the amount of regenerative energy changes according to the duty ratio of the PWM control, a power source voltage, continuation time Td of the alternating mode, reflux mode execution time after the alternating mode, etc. The CPU 18 controls the amount of the regenerative energy by suitably regulating these values.

Further, the CPU 18 always monitors the voltage of the battery 16, and conducts a PI control by a voltage feedback, thereby preventing the battery 16 from being overcharged. In this case, the PWM duty ratio and the continuation time in the alternating mode may be suitably controlled while observing the battery voltage so as to ~~make~~set the battery voltage at a predetermined value. Note that, in the PWM control, stability of the voltage value is important to ensure the control accuracy, and the detection of the battery voltage is also important in this point.

As shown in FIG. 4(c), in the controlling method, since the reflux mode is once executed after the alternating mode, the reflux mode is switched to the regenerative mode in the state ~~that~~in which the winding current rate is increased. Therefore, an amount of the regenerative energy (a area of a portion R) at the regenerative mode execution time (portion R in FIG. 4(c)) can be made large, and a power generating efficiency can be raised. Here, a rising trend of the current rate in the reflux mode is determined depending on the current value and the

rotational speed of the rotor at the reflux mode starting time. If they are not sufficiently large, the current value does not increase at the reflux mode time. When the current increase at the reflux mode time is not sufficient, the amount of the
5 regenerative energy in the regenerative mode can not be ensured, therefore the power generating efficiency is lowered. On the contrary, when the winding current is controlled so as to increase the current value at the reflux mode starting time, as a result of this, the brake force increases. In the controlling
10 method of the present embodiment, an average current value in a region for generating a brake force by the winding current is suppressed by the alternating mode, and the current value at the reflux mode starting time can be controlled to become as large as possible while suppressing such a brake force. Therefore,
15 the brake force and the amount of the regenerative energy can be controlled in a well-balanced manner, and the power generating efficiency is improved.

Incidentally, since the SR motor is executed by the PWM control in a normal motoring operation in many cases, the power
20 generation operation can be performed in the above-mentioned control state without introducing a new circuit or control mode. Therefore, the existing apparatus can deal with the controlling method of the present invention, and power generating efficiency can be improved without increasing the cost.

25 (Embodiment 2)

In the meantime, in order to increase the power generation rate in a control method as in the embodiment 1, it is necessary to increase a winding current value in the alternating mode. To this end, there arises a need to raise the

ON duty ratio under the PWM control in an alternating mode time or to lengthen the energizing time. However, when the winding current value in the alternating mode time is increased, there is a problem that the current value in the reflux mode executed
5 after the alternating mode excessively increases. That is, as shown in FIG. 5, the maximum value i_{max} of the winding current value i becomes large. If the winding current value i excessively increases, a load on the power device is increased, and hence elements of large capacity must be used, and which
10 thereby ~~to increase~~ increases the cost.

In this case, as in the above-mentioned Japanese Patent Application Laid-Open Publication No. 2001-78490, when the reflux mode and the regenerative mode are switched while monitoring the current value, the excess current can be
15 suppressed, and the load on the power device can be alleviated. However, to monitor the current value, a sensor for detecting the current value and a feedback control circuit operating at a high speed are necessary. That is, when a current monitor system is adopted, the load on the power device can be
20 alleviated but since the sensor, the high-speed comparator, etc., are newly used, the problem of cost increase is ~~not still~~ still not solved. Therefore, the present inventor has considered the structure of the embodiment to prevent the excessive current generation in the generator of the SR motor structure without
25 increasing the cost.

FIG. 6 is a circuit diagram showing only the U-phase portion extracted from the circuit diagram of FIG. 2; and FIG. 6(a) shows the supply mode, FIG. 6(b) shows the regenerative mode, and FIGS. 6(c) and 6(d) show the reflux mode in the

controlling method of the embodiment 2 of the present invention. Incidentally, in the following embodiment, the structures of the generator and its drive circuit are similar to those shown in FIGS. 1 and 2, and the similar members and parts, etc. are
5 designated by the same reference numbers, and therefore the description will be omitted.

In the controlling method of this embodiment, the generator 1 is driven in three control modes ~~of including~~ the supply mode, the regenerative mode and the reflux mode. Here,
10 different from the embodiment 1, there are two ~~ways~~ variations of the reflux mode as shown in FIGS. 6(c) and 6(d). First, in the case of FIG. 6(c), the FET 11U is turned OFF, and the FET 12U is turned ON. Also in this state, the power supply to the windings 5Ua, 5Ub from the battery 16 is stopped, and
15 electromotive forces are generated in the windings 5Ua, 5Ub. In this mode, the current flows in a route through the diode 13U, the winding set 5U and the FET 12U by the electromotive forces. That is, both ends of the winding set 5U are grounded, and the current refluxes through the aforementioned route during the
20 reflux mode.

In the case of FIG. 6(d), the FET 11U is turned ON, and the FET 12U is turned OFF. At this time, both ends of the windings 5Ua, 5Ub are connected to the battery 16 to be the same potential, and an electromotive force is generated in the
25 windings 5Ua, 5Ub. The current flows in the route through the FET 11U, the winding set 5U, and the diode 14U, and the current refluxes the route during the reflux mode.

In the controlling method of the generator according to the present invention, the above-mentioned three types of ~~the~~

modes are performed as described below. FIG. 7 is an explanatory view showing execution timing of each mode in the U-phase in the controlling method of the embodiment 2 of the present invention. Any of the abscissa axes of FIG. 7 show a rotary angle of the rotor 3. FIG. 7(a) shows the relationship between the rotary angle of the rotor and the inductance L, FIG. 7(b) shows the energizing state of the HI side and the LO side in the drive circuit, FIG. 7(c) shows the relationship between the rotary angle of the rotor and the winding voltage, and FIG. 7(d) shows the relationship between the rotary angle of the rotor and the winding current. Here, the U-phase will be described as an example,~~however.~~ However, similar control is performed for the V-phase and the W-phase.

As shown in FIG. 7, in this embodiment, when the inductance L becomes the maximum value L_{max} (change rate $(dL/d\theta)$ of the inductance L is "0"), the power supply is started to the winding 5. The power supply to the winding 5 is PWM controlled by the gate driver 15U. That is, the supply current rate to the winding 5 is controlled by the continuation time and the duty ratio under the ON/OFF control of the FET 11U or the like, and a first alternating mode C_1 for alternatively repeating the supply mode and the reflux mode is performed.

In the first alternating mode C_1 , the FET 11U of the HI side is controlled by a predetermined duty ratio, and the FET 12U of the LO side is always set to the ON state. When the FET 11U of the HI side is ON, it becomes the state shown in FIG. 6(a), and the supply mode is performed. On the contrary, when the FET 11U of the HI side is OFF, it becomes the state shown in FIG. 6(c), and the reflux mode is executed. The continuation

time T_d of the first alternating mode C_1 is set in response to the rotational speed of the rotor calculated from the signal of the shaft position sensor 17. At this time, T_d can be set by the rotary angle of the rotor, or may be set to a predetermined
5 angle irrespective of the rotational speed or to an angle in response to the rotational speed.

During the first alternating mode C_1 , the winding current increases at the supply mode execution time (portion P in FIG. 7(d)), while the winding current decreases at the reflux mode
10 execution time (portion Q in FIG. 7(d)). In the first alternating mode C_1 , the reduction part of the winding current in the reflux mode Q is smaller than the increase part of the winding current in the supply mode P, and the PWM duty ratio is set so that the current waveform generally increases in the
15 sawtooth-like waveform during the time T_d . After the time T_d is elapsed, the CPU 18 switches the operation mode to a second alternating mode C_2 . In the second alternating mode C_2 , the reflux mode Q and the regenerative mode (portion R in FIG. 7(d)) are alternately repeated.

20 The rising trend of the current rate of the reflux mode Q (particularly Q_e) in the second alternating mode C_2 is determined depending upon the current value and the rotational speed of the rotor at the reflux mode starting time, and if they are not sufficiently large, the current value does not increase
25 at the reflux mode time. When the current increase at the reflux mode time is not sufficient, the amount of the regenerative energy in the regenerative mode cannot be ensured, therefore the power generating efficiency is lowered. On the contrary, when the winding current is controlled so as to

increase the current value at the reflux mode starting time, as
a result of the brake force increases. Therefore, in the
controlling method of the present embodiment, an average current
value in a region for generating a brake force by the winding
5 current is suppressed by the first alternating mode C_1 , and the
current value at the reflux mode starting time in the second
alternating mode C_2 can be controlled to become as large as
possible while suppressing such a brake force.

In the second alternating mode C_2 , with use of the PWM
10 control, the FET 11U of the HI side is turned ON/OFF even after
the first alternating mode C_1 , and the reflux mode after
executing the first alternating mode C_1 is chopped. Here, in
the controlling method of the embodiment 1 as shown in FIG. 5,
only the reflux mode is performed after the first alternating
15 mode C_1 is executed, to increase the winding current, then the
regenerative mode is performed to increase the amount of the
regenerative current. However, as described above, there is the
case ~~that~~ in which the winding current increases excessively by
the reflux mode after the first alternating mode C_1 is carried
20 out, and hence there is a problem that the load on the power
device increases.

On the contrary, in the controlling method of the
embodiment 2, the reflux mode and the regenerative mode are not
merely executed after the first alternating mode C_1 is performed,
25 but the reflux mode and the regenerative mode are repeatedly
executed, and the increase in the winding current in the reflux
mode is suppressed suitably in the regenerative mode. Thus, as
compared with the case ~~that~~ in which the winding current is
simply increased in the reflux mode as shown in FIG. 5, as

apparent from FIG. 7, in the controlling method for performing the second alternating mode C_2 , the maximum current value i_{\max} can be suppressed to a low value.

At the final stage of the second alternating mode C_2 , only the regenerative mode is performed. At the regenerative mode execution time, the winding voltage becomes $-E$, and in the final regenerative mode R_e , the winding current value i is gradually reduced to become "0" shortly. Thus, energy of an amount shown by an area of a portion R of FIG. 7(d) is regenerated to the battery 16. Here, the amount of the regenerative energy in the final regenerative mode R_e depends upon the current amount at the regenerative mode R_e starting time. Therefore, normally, when the maximum current value i_{\max} is suppressed, the amount of the regenerative current in the regenerative mode R_e is also reduced. That is, in the regenerative mode R_e of FIG. 7, a large area (amount of the regenerative energy) as in the regenerative mode R of FIG. 5, cannot be secured.

However, in the controlling method of the present embodiment, the reflux mode is executed in the second alternating mode C_2 , and the winding current is increased therein. Further, the regenerative mode R is provided before the regenerative mode R_e . Thus, as compared with the case ~~that~~ in which the regenerative mode is merely executed after the first alternating mode C_1 , the amount of the regenerative current is increased for the current increased part due to the reflux mode, and the regenerative current is obtained even in the regenerative mode on the way. Therefore, since the amount of the regenerative energy in the regenerative mode R_e is lower than the case shown in FIG, 5, the entire amount of the

regenerative energy is sufficiently ensured.

Incidentally, since the amount of the regenerative energy is decided according to the amount of current at the regenerative mode starting time, the amount of the regenerative energy changes according to the duty ratio of the PWM control, the power source voltage, the continuation time T_d of the first alternating mode C_1 , the number of times of alternating after the first alternating mode C_1 , etc. Therefore, the CPU 18 controls the amount of the regenerative energy by suitably regulating these values. Further, the CPU 18 always monitors the voltage of the battery 16, and performs a PI control by a voltage feedback, thereby preventing the battery 16 from being overcharged. In this case, the PWM duty ratio and the continuation time in the alternating mode may be suitably controlled while observing the battery voltage so as to ~~make-set~~ the battery voltage at a predetermined value. In the PWM control, stability of the voltage value is important to ensure the control accuracy, and the detection of the battery voltage is also important in this point.

Thus, according to the controlling method of the embodiment 2 of the present invention, the amount of the regenerative current can be ensured to achieve the maximum limit while suitably suppressing the maximum current value i_{max} , and the power generation in a well-balanced manner between them can be performed. Accordingly, a load on the power device is reduced, an element having a large capacity is not required, and the cost can be reduced. Further, the amount of the winding current can be suppressed without adding a current sensor, a high speed comparator or the like, and an increase in cost due

to the increase in the number of components can be prevented.

(Embodiment 3)

Then, as the embodiment 3, the case ~~that~~ in which
starting timing of the first alternating mode C_1 is advanced
5 from a position where the inductance L becomes the maximum value
 L_{max} , will be described. When the control as shown in FIG. 5 is
performed, a measure that the executing time T_d of the
alternating mode is increased, times of a reflux mode and a
regenerative mode are relatively reduced, and the maximum
10 current value i_{max} is suppressed, is considered. However, when
such a measure is adopted, as the times of the reflux mode and
the regenerative mode decrease, there is a possibility that a
sufficient amount of power generation cannot be obtained.

Then, starting timing of the alternating mode is advanced
15 to increase an amount of current to a certain degree at the
reflux mode starting time after the alternating mode. That is,
a control state of advancing an angle may be considered.
Particularly, since the winding current becomes an inductance
load, even if the first alternating mode is started, the winding
20 current might not rise in an ideal shape as shown in FIG. 7 in
many cases. On the other hand, when the first alternating mode
 C_1 is started before the L_{max} time point by means of the lead
angle, the amount of the winding current can be effectively
increased at the L_{max} time point, and the power generating
25 efficiency is improved.

The controlling method of the present invention is
effective even when such a lead angle is performed. FIG. 8 is
an explanatory view showing execution timing of each mode when
the lead angle control is performed, and shows the control state

when the above-mentioned lead angle is performed. In FIG. 8, any of the abscissa axes show a rotary angle of a rotor 3 similarly to FIG. 7. FIG. 8(a) shows the relationship between the rotary angle of the rotor and the inductance L, FIG. 8(b) shows the energizing states of the HI side and the LO side in the drive circuit, FIG. 8(c) shows the relationship between the rotary angle of the rotor and the winding voltage, and FIG. 8(d) shows the relationship between the rotary angle of the rotor and the winding current. Here, the U-phase will be described as an example,~~however.~~ However, similar control is performed for the V-phase and the W-phase.

As shown in FIG. 8, in this embodiment, before the inductance L becomes the maximum value L_{max} , the power supply to the winding 5 is started. In this case, at an FET 11U of the HI side, the power supply is started at a point in time ~~point of~~ advancing a time T_{ah} from the time point of L_{max} , and at an FET 12U of the LO side, the power supply is started at a point in time ~~point of~~ advancing a time T_{al} from the time point of L_{max} . The respective lead angle times T_{ah} , T_{al} are set corresponding to the amount of the winding current at the time of starting the second alternating mode C_2 , that is, ON duty ratio of the FET 11U of the HI side. That is, when the ON time is lengthened, the value of the current rise in the first alternating mode C_1 is increased, but even when the amount of the winding current at the second alternating mode C_2 starting time becomes insufficient, the lead angle control is performed to lengthen the continuation time T_d of the first alternating mode C_1 . In this embodiment, $T_{al} > T_{ah}$ is set, but the T_{al} and the T_{ah} may be the same time ($T_{al} = T_{ah}$).

The first alternating mode C_1 is started from a point in
time ~~point~~ (time T_{ah} lead angle position) when the FET 11U of
the HI side is turned ON. The first alternating mode C_1 is
executed under the PWM control by the gate driver 15U, similarly
5 to the embodiment 2, and a supply mode P and a reflux mode Q are
alternately repeated. After the time T_d is elapsed, the CPU 18
switches the operation mode to a second alternating mode C_2 . In
the second alternating mode C_2 , similarly to the embodiment 1,
the reflux mode Q and the regenerative mode R are alternately
10 repeated to thereby suppress the maximum current value i_{max} .

In the controlling method of this embodiment, since the
continuation time T_d of the first alternating mode C_1 is
lengthened by means of the lead angle, the amount of current at
the second alternating mode C_2 starting time is increased. Thus,
15 as shown in FIG. 7, it is effective when the first alternating
mode C_1 is started from the L_{max} time point, and the amount of
the power generation becomes in short supply. As the same time,
in the second alternating mode C_2 , since the increase in the
amount of current is suppressed, the excess increase in the
20 amount of the winding current in the reflux mode can be
suppressed.

According to the controlling method of the embodiment 3,
by combining the increase in the amount of current by means of
the lead angle and the suppression of the amount of current in
25 the second alternating mode C_2 in a well-balanced manner, the
preferable control state capable of sufficiently securing the
amount of the regenerative current can be realized while
suppressing the maximum current value i_{max} . Therefore, the
amount of the power generation can be increased while the

increase in the load on the power device is suppressed to the minimum limit, and a cost rise due to the use of a large capacity element can be prevented. Further, the amount of the winding current can be suppressed without adding a current
5 sensor, a high-speed comparator or the like, and an efficient power generation can be performed without increasing the cost.

The present invention is not limited to the above-described embodiments, and various changes and modifications may be made without departing from the spirit and scope of the
10 present invention.

For example, in the above-described embodiment, at the time point that the inductance L becomes the maximum value L_{max} , the alternating mode is started. However, the alternating mode can be started from not exactly the L_{max} time point but its
15 vicinity. When the rotor 3 rotates at a high speed, it is difficult to secure a current value at the reflux mode starting time, ~~then~~. Therefore, a lead angle control for starting the alternating mode before the maximum value L_{max} position may be performed to increase the current value. Accordingly, the
20 alternating mode continuation time can be secured longer, and the current value at the reflux mode starting time can be raised, and it is particularly effective when the voltage generation is low.

In the above-described embodiment, the battery voltage is
25 monitored by the CPU 18. However, a current amount detector may be provided in the control circuit, and the current amount is monitored to set the duty ratio of the PWM control, the alternating mode continuation time T_d , the reflux mode execution time after the alternating mode, and so on. Note, however, that

the voltage detection is generally easy as compared with the current amount detection, and the voltage detection is advantageous in cost.

Furthermore, in the embodiments 2 and 3, the case that
5 the duty ratio of the FET 11U of the HI side is set similarly in the first alternating mode C_1 and the second alternating mode C_2 , has been described. However, the duty ratios in the modes C_1 and C_2 may be set to different values. In addition, the
10 embodiments 2 and 3 are described ~~in-for~~ the case that in which the FET of the HI side is used for the PWM drive, and the FET of the LO side is used for a phase control. However, the FET of the LO side may be used for the PWM drive and the FET of the HI side may be used for the phase control.

On the one hand, the generator according to the present
15 invention may be used as a power generation facility of a wind power generator. In the wind power generator, rotary blades are operated by ~~a~~-wind power to conduct power generation, and a large wind power is required at the starting time of the rotary blade, ~~a.~~ A generator cannot be started if a-the wind is not
20 ~~blown by~~ does not have a wind speed of a certain degree.

Therefore, in the case of a slight breeze ~~state~~ that does not satisfy a wind speed capable of starting the rotary blade, there is a problem that ~~a~~-power generation cannot be performed even if the wind blows.

25 ~~Whereas~~ In that case, this generator can be used as an SR motor. It is possible to use the generator as a motor to start the rotary blade, and after the rotary blade is once started, to use the generator as a generator. Therefore, even in the case of the above-mentioned slight breeze ~~state~~, the rotary blade can

be started by the motor, and thereafter the rotary blade can be rotated by the wind power. In this case, the using time of the generator as the motor is short, and acquisition energy by the power generation thereafter is much larger. Thus, the wind
5 power generator can be operated from the slight breeze state, and the power generating efficiency can be improved.

ABSTRACT

When drive control of a generator is performed, PWM control of a switching circuit comprising an FET and a diode connected to the opposite ends of a winding is performed. In the vicinity of a moment in time L_{max} where the winding has a maximum inductance L , an alternating mode for repeating a supply mode and a reflux mode alternately is performed through PWM control. After the alternating mode is performed, the reflux mode is performed temporarily in order to increase the quantity of current, and then a regenerative mode is performed. The regenerative mode is performed by increasing the current level as much as possible when the reflux mode is started while suppressing the brake force of the rotor in the alternating mode. From a position advancing in angle by a time T_{ah} from the a- moment in time L_{max} where the winding has a maximum inductance L , a first alternating mode C_1 for repeating the supply mode P and the reflux mode Q alternately is performed. After the first alternating mode C_1 is performed, a second alternating mode C_2 for repeating the reflux mode Q and the regenerative mode R alternately is performed.